


GBJ5006L


Single-Phase 50A Glass Passivated Bridge Rectifier



Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Plastic material-UL flammability 94V-0
- This is a Pb - Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

Circuit Diagram



Mechanical Data

- Case: GBJ, Molded plastic
- Terminals: Plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting Position: Any
- Lead Free: For RoHS / Lead Free Version
- Weight: 6.8 grams(approx)

Maximum Ratings @T_A=25°C unless otherwise specified

Type Number	Symbol	GBJ5006L	Units
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_{DC}	600	V
RMS Reverse Voltage	V_{RMS}	420	V
Average Rectified Output Current (Note 2) @T _c = 90°C	$I_{(AV)}$	50	A
Peak Forward Surge Current,8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	450	A
I ² t Rating for Fusing (t<8.3ms)	I ² t	840.375	A ² s

Electrical Characteristics@T_A=25°C unless otherwise specified

Type Number	Symbol	GBJ5006L	Units
Forward Voltage per element @I _F =25A	V _F	0.97	V
Peak Reverse Current @T _A = 25°C At Rated DC Blocking Voltage @T _A = 125°C	I _{RM}	5 500	μA
Dielectric Strength	V _{ids}	2500	V
The proposed installation torque Max torque	T _{or}	Typ. 5.0 Max 8.0	Kgf.cm
Typical Junction Capacitance(Per Element) (Note 1)	C _J	85	pF

* Pulse width < 300 μs, duty cycle < 2%



Thermal-Mechanical Specifications:




Type Number	Symbol	GBJ5006L	Units
Between junction and case, With heatsink	R _{θjc}	1	°C/W
Between junction and ambient, Without heatsink	R _{θja}	22	
Operating and Storage Temperature Range	T _J , T _{STC}	-55 to +150	°C

Note: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Thermal resistance from junction to case per element. Unit mounted on 75 x 75 x 1.6mm aluminum plate heat sink.

Ratings and Characteristics Curves






Ordering Information

Device	Package	Plating	Shipping
GBJ5006L	GBJ(Pb-Free)	Pure Sn	15pcs / tube

Marking Diagram




Where XXXXX is YYWWL

SSG = SSG
YY = Year
WW = Week
L = Lot Number
GBJ5006L = Type Number

Cautions: Molding resin
Epoxy resin UL94V-0

Mechanical Dimensions GBJ (Inches/Millimeters)



Dimensions	Millimeters		Inches	
	Min	Max	Min	Max
A	29.7	30.3	1.169	1.193
B	10.8	11.2	0.425	0.441
C	1.9	2.3	0.075	0.091
D	0.9	1.1	0.035	0.043
E	9.8	10.2	0.386	0.402
F	7.3	7.7	0.287	0.303
G	17.0	18.0	0.699	0.709
H	4.40	4.80	0.173	0.189
I	19.7	20.3	0.776	0.799
J	4.8	5.2	0.189	0.205
K	4.4	4.8	0.173	0.189
L	3.4	3.8	0.134	0.150
M	3.1	3.4	0.122	0.134
N	4.4	4.8	0.173	0.189
O	2.5	2.9	0.098	0.114
P	0.6	0.8	0.023	0.031



DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.