


GBJ35005-GBJ3510


Single-Phase 35.0A Glass Passivated Bridge Rectifier



Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Plastic material-UL flammability 94V-0
- This is a Pb - Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

Circuit Diagram



Mechanical Data

- Case: GBJ, Molded plastic
- Terminals: Plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting Position: Any
- Lead Free: For RoHS / Lead Free Version
- Weight: 6.8 grams(approx)

Maximum Ratings @ $T_A=25^\circ\text{C}$ unless otherwise specified

Type Number	Symbol	GBJ 35005	GBJ 3501	GBJ 3502	GBJ 3504	GBJ 3506	GBJ 3508	GBJ 3510	Units
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_{DC}	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Average forward rectified output current (with heatsink)@ $T_C = 100^\circ\text{C}$ (without heatsink)@ $T_A = 25^\circ\text{C}$	$I_{(AV)}$				35				A
Peak Forward Surge Current,8.3ms single half-sine-wave superimposed on rated load (JEDEC method) @ $T_J = 25^\circ\text{C}$ @ $T_J = 125^\circ\text{C}$	I_{FSM}				3.6	450	360		A
I^2t Rating for Fusing ($t < 8.3\text{ms}$)	I^2t				840				A^2s

Electrical Characteristics@ $T_A=25^\circ\text{C}$ unless otherwise specified

Type Number	Symbol	GBJ 35005	GBJ 3501	GBJ 3502	GBJ 3504	GBJ 3506	GBJ 3508	GBJ 3510	Units
Forward Voltage (per element) @ $I_F = 17.5\text{A}$	V_F				1.05				V
Peak Reverse Current @ $T_A = 25^\circ\text{C}$ At Rated DC Blocking Voltage @ $T_A = 125^\circ\text{C}$	I_{RM}			5	200				μA
The proposed installation torque Max torque	T_{or}					Typ. 5.0 Max. 8.0			Kgf.cm
Typical Junction Capacitance(per leg) (Note 1)	C_J				140				pF

* Pulse width < 300 μs , duty cycle < 2%

Thermal-Mechanical Specifications:

Type Number	Symbol	GBJ 35005	GBJ 3501	GBJ 3502	GBJ 3504	GBJ 3506	GBJ 3508	GBJ 3510	Units
Typical Thermal Resistance Junction	$R_{\theta JA}$ $R_{\theta JL}$ $R_{\theta JC}$			18	1.5	0.8			$^\circ\text{C}/\text{W}$
Operating and Storage Temperature Range	T_J, T_{STG}				-55 to +150				$^\circ\text{C}$

Note: 1- Measured at 1 MHZ and applied reverse voltage of 4.0 VDC.

Ratings and Characteristics Curves

Fig. 1 Output Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Forward Surge Current Capability






Fig. 4 Typical Reverse Characteristics



Ordering Information

Device	Package	Plating	Shipping
GBJ35005 THRU GBJ3510	GBJ(Pb-Free)	Pure Sn	15pcs / tube

Marking Diagram





Where XXXXX is YYWWL

SSG	= SSG
YY	= Year
WW	= Week
L	= Lot Number
GBJ35005	= Type Number

Cautions: Molding resin
Epoxy resin UL:94V-0

Mechanical Dimensions GBJ (Inches/Millimeters)



Dimensions	Millimeters		Inches	
	Min	Max	Min	Max
A	29.7	30.3	1.169	1.193
B	10.8	11.2	0.425	0.441
C	1.9	2.3	0.075	0.091
D	0.9	1.1	0.035	0.043
E	9.0	11.0	0.354	0.433
F	7.3	7.7	0.287	0.303
G	17.0	18.0	0.699	0.709
H	3.8	4.2	0.150	0.165
I	19.7	20.3	0.776	0.799
J	4.8	5.2	0.189	0.205
K	4.4	4.8	0.173	0.189
L	3.4	3.8	0.134	0.150
M	3.1	3.4	0.122	0.134
N	4.4	4.8	0.173	0.189
O	2.4	2.8	0.094	0.110
P	0.5	0.7	0.020	0.028

Technical Data
Data Sheet N1805, Rev. D**DISCLAIMER:**

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.