



S4M0044120K Silicon Carbide Power MOSFET



Features

- Positive temperature characteristics, easy to parallel.
- Low on-resistance typ. $R_{DS(on)} = 44 \text{ m}\Omega$.
- Fast switching speed and low switching losses.
- Very fast and robust intrinsic body diode.
- Process of non-bright tin electroplatin.
- “-A” is an AEC-Q101 qualified device.

Circuit Diagram



Applications

- EV Fast Charging Modules
- EV On Board Chargers
- Solar Inverters
- Online UPS/Industrial UPS
- SMPS (Switch Mode Power Supplies)
- DC-DC Converters
- ESS (Energy Storage Systems)

Maximum Ratings($T_c = 25^\circ\text{C}$ unless otherwise specified)

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Units	Note
Drain - Source Voltage	V_{DSmax}	$V_{GS} = 0 \text{ V}$, $I_D = 100 \mu\text{A}$			1200	V	
Gate - Source Voltage (dynamic)	V_{GSmax}	AC ($f > 1 \text{ Hz}$)	-8		+22	V	
Gate - Source Voltage (static)	V_{GSop}	Static		-4 / +18		V	[1]
Continuous Drain Current	I_D	$V_{GS} = 18 \text{ V}$, $T_c = 25^\circ\text{C}$ $V_{GS} = 18 \text{ V}$, $T_c = 100^\circ\text{C}$			57 41	A	
Pulsed Drain Current	$I_{D(pulse)}$	Pulse width t_p limited by T_{jmax}			147	A	
Power Dissipation	P_D	$T_c = 25^\circ\text{C}$			338	W	

[1] Recommended turn off gate voltage is -4 V. Recommended turn on gate voltage is 18 V. Do not use with $V_{GSON} < 12 \text{ V}$.

Electrical Characteristics:

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Units
Drain Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 100\text{ }\mu\text{A}$	1200			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 10.6\text{ mA}$	2	2.8	4	V
		$V_{DS} = V_{GS}, I_D = 10.6\text{ mA}, T_J = 175\text{ }^\circ\text{C}$		1.9		V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 1200\text{ V}, V_{GS} = 0\text{ V}$			100	μA
Gate Source Leakage Current	I_{GSS}	$V_{GS} = 18\text{ V}, V_{DS} = 0\text{ V}$			250	nA
Drain Source On-State Resistance	$R_{DS(on)}$	$V_{GS} = 18\text{ V}, I_D = 28.6\text{ A}$		44	52	m Ω
		$V_{GS} = 18\text{ V}, I_D = 28.6\text{ A}, T_J = 175\text{ }^\circ\text{C}$		73		m Ω
Transconductance	g_{fs}	$V_{DS} = 20\text{ V}, I_{DS} = 28.6\text{ A}$		14		S
		$V_{DS} = 20\text{ V}, I_{DS} = 28.6\text{ A}, T_J = 175\text{ }^\circ\text{C}$		13		S
Input Capacitance	C_{ISS}	$V_{GS} = 0\text{ V}$		1337		pF
Output Capacitance	C_{OSS}	$V_{DS} = 1200\text{ V}$		76		
Reverse Transfer Capacitance	C_{RSS}	$V_{AC} = 25\text{ mV}$		1.5		
COSS Stored Energy	E_{OSS}	$f = 1\text{ MHz}$		63		μJ
Turn-On Switching Energy	E_{ON}	$V_{DS} = 800\text{ V}, V_{GS} = -4 / 18\text{ V}$		92		μJ
Turn-Off Switching Energy	E_{OFF}	$I_D = 28.6\text{ A}, R_{G(ext)} = 2.5\text{ }\Omega, L = 99\text{ }\mu\text{H}$		70		
Turn-On Delay Time	$t_{d(on)}$	$V_{DS} = 800\text{ V}, V_{GS} = -4 / 18\text{ V}$		7.6		ns
Rise Time	t_r	$I_D = 28.6\text{ A}, R_{G(ext)} = 2.5\text{ }\Omega$		9.0		
Turn-Off Delay Time	$t_{d(off)}$	Inductive Load Timing relative to		12.9		
Fall Time	t_f	V_{DS} Per IEC60747-8-4 pg 83		6.4		
Internal Gate Resistance	$R_{G(int)}$	$f = 1\text{ MHz}, AC = 25\text{ mV}$		1.5		Ω
Gate to Source Charge	Q_{gs}	$V_{DS} = 800\text{ V}, V_{GS} = -4 / 18\text{ V}$		14		nC
Gate to Drain Charge	Q_{gd}	$I_D = 28.6\text{ A}$		10		
Total Gate Charge	Q_g	Per IEC60747-8-4 pg 21		48		

Reverse Diode Characteristics (TA= 25 °C, unless otherwise specified)

Characteristics	Symbol	Conditions	Typ.	Max.	Units
Diode Forward Voltage	V _{SD}	V _{GS} = -4 V, I _{SD} = 14.3 A	3.9		V
	V _{SD}	V _{GS} = -4 V, I _{SD} = 14.3 A, T _J = 175°C	3.4		V
Reverse Recovery Time	t _{rr}	V _{GS} = -4 V, I _{SD} = 28.6 A, T _J = 25 °C	14		ns
Reverse Recovery Charge	Q _{rr}	V _R = 800 V	207		nC
Peak Reverse Recovery Current	I _{mm}	di / dt = 2000 A / μs	17		A

Thermal-Mechanical Specifications

Characteristics	Symbol	Condition	Specification	Units
Junction Temperature	T _J	-	-55 to +175	°C
Storage Temperature	T _{stg}	-	-55 to +175	°C
Typical Thermal Resistance Junction to Case	R _{θJC}		0.44	°C /W

Ordering Information

Device	Package	Shipping
S4M0044120K	TO-247-4	30 pcs/tube

Marking Diagram



Where XXXXX is YYWWL

S4M = Device Type
 0044 = RDS(on)
 120 = Reverse Voltage (1200V)
 K = Package
 SSG = SSG
 YY = Year
 WW = Week
 L = Lot Number

Cautions: Molding resin
 Epoxy resin UL94V-0

Ratings and Characteristics Curves




Figure 1. Output Characteristics $T_J = -55^\circ\text{C}$




Figure 2. Output Characteristics $T_J = 25^\circ\text{C}$




Figure 3. Output Characteristics $T_J = 175^\circ\text{C}$




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current
For Various Temperatures




Figure 6. On-Resistance vs. Temperature
For Various Gate Voltage

Technical Data
Data Sheet N3267, Rev.-




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at $T_J = -55\text{ }^{\circ}\text{C}$




Figure 9. Body Diode Characteristic at $T_J = 25\text{ }^{\circ}\text{C}$




Figure 10. Body Diode Characteristic at $T_J = 175\text{ }^{\circ}\text{C}$




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristic




Figure 13. 3rd Quadrant Characteristic at $T_j = -55\text{ }^{\circ}\text{C}$




Figure 14. 3rd Quadrant Characteristic at $T_j = 25\text{ }^{\circ}\text{C}$




Figure 15. 3rd Quadrant Characteristic at $T_j = 175\text{ }^{\circ}\text{C}$




Figure 16. Output Capacitor Stored Energy




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200 V)




Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1200V)




Figure 19. Continuous Drain Current Derating vs. Case Temperature




Figure 20. Maximum Power Dissipation Derating vs. Case Temperature




Figure 21. Transient Thermal Impedance (Junction - Case)




Figure 22. Safe Operating Area




Figure 23. Clamped Inductive Switching Energy vs. Drain Current ($V_{DD} = 800V$)




Figure 24. Clamped Inductive Switching Energy vs. $R_{G(ext)}$




Figure 25. Clamped Inductive Switching Energy vs. Temperature





Figure 26. Switching Times vs. $R_{G(ext)}$

Mechanical Dimensions TO-247-4



SYMBOL	mm		
	Min	Nom	Max
A	4.80	5.00	5.20
A1	2.23	2.41	2.59
A2	1.85	2.00	2.15
b	1.11	1.21	1.36
b1	2.35	2.55	2.75
c	0.51	0.61	0.75
D	23.30	23.45	23.60
D1	16.25	16.55	16.85
E	15.75	15.94	16.10
E1	13.00	13.26	13.43
E2	4.00	4.30	4.60
E3	1.15	1.45	1.75
e		2.54BSC	
e1		5.08BSC	
L	17.31	17.47	17.82
L1	1.50	1.70	1.90
ØP	3.51	3.60	3.65
ØP1	7.08	7.19	7.30
S		6.15BSC	

The outline from different package houses may have slight differences.
So the outline above is just schematic. The dimensions are controlled per specifications.

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment , and safety equipment) , safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement .
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.